



www.impactwiremarking.com

AWMS-402TT WIRE MARKER & LABEL PRINTER



PRINTER SPECIFICATIONS INCLUDE:

Speed	3 ips (76 mm/s)
Print Resolution	203 dpi (8 dots/mm)
Graphics & Bar Codes	Code 39, Extended Code 39, Code 93, Code 128 UCC, Code 128 (Subset A,B,C), Codabar, Interleave 2 of 5 EAN-8 2&5 add on, EAN-13, EAN-128, UPC, UPC-A E 2&5 add on, POSTNET, German POST, Matrix 25 Maxicode, PDF-417, PCX, BMP, GDI graphics.
Print Width	1.0" - 4.13" (25-105mm)
Print Method	Thermal Transfer
Media Size	Max width 4.3" (110mm) Min width 1.0" (25mm) Min length 0.4" (10mm) Thickness .0025"-.01" (.0635mm-.245mm). Max roll capacity 4.3" O.D. Core size 1.0" I.D.
Media Type	Heat Shrinkable Wire Markers, labels on roll, die-cut, fan-fold, tags, ticket, or synthetics.

Indexing	Black Bar and Gap TOF
Ribbon	Resin. Ribbon width 1.0" - 4.3" Ribbon roll Max O.D. 1.4" Core size 0.5" core I.D. Ribbon length 298'
Memory/Buffer	512K standard, 512K expandable
Software	Windows driver (98/XP/2000) Label creation software included.
Interface	RS-232 serial, Centronics parallel.
Physical/Electrical	W 7.3" x D 10.9" x H 6.0" 4.6 lbs. (2.1 Kgs) 110/220 VAC ± 10%, 50/60 Hz CE,UL,CUL
Environmental	40°F - 100°F (4°C-38°C) 10%-90% non condensing FCC Class B emissions