



www.impactwiremarking.com

AWMS-4402TT WIRE MARKER & LABEL PRINTER



PRINTER SPECIFICATIONS INCLUDE:

Speed	Variable 2 to 4 ips.
Print Resolution	203 dpi (8 dots/mm)
Graphics & Bar Codes	Code 39, Extended Code 39, Code 93, Code 128 UCC, Code 128 (Subset A,B,C), Codabar, Interleave 2 of 5 EAN-8 2&5 add on, EAN-13, EAN-128, UPC, UPC-A E 2&5 add on, POSTNET, German POST, Matrix 25 Maxicode, PDF-417, PCX, BMP, GDI graphics.
Print Width	1.0" - 4.09" (25-104mm)
Print Method	Thermal Transfer
Media Size	Max width 4.3" (110mm) Min width 1.0" (25mm) Min length 0.4" (10mm) Thickness .0025"-.01" (.0635mm-.245mm). Max roll capacity 8" (203mm) O.D. Core size 1.5" - 3" (38mm - 76mm) I.D. Back feed slot.
Media Type	Heat Shrinkable Wire Markers, labels on roll, die-cut, fan-fold, tags, ticket, or synthetics.

Indexing	Black Bar, Notch and Gap TOF
Ribbon	Resin. Ribbon width 4.18" Ribbon roll Max O.D. 3" Core size 1" core I.D. Ribbon length 984'
Memory/Buffer	512K DRAM, 512K Flash
Software	Windows driver (98/XP/2000) Label creation software included.
Interface	RS-232 serial, Centronics parallel.
Physical/Electrical	W 9.8" x H 10.2" x L16.0" 24.6 lbs. (11 Kgs) 110/220 VAC ± 10%, 50/60Hz CE, UL, CUL, FCC class A
Environmental	40°F - 100°F (4°C-38°C) 10%-90% non condensing FCC Class A emissions