



www.impactwiremarking.com



## K4100 Desktop Industrial Label Printer

The **K4100** Desktop Industrial Label Printer is unlike most desktop printers **K4100** offers a versatile line of supplies including industrial labels, self laminating wire wraps and shrink tube. This flexibility makes labeling easy with **K4100** Desktop for any application. The **K4100** also connects to your PC for you to customize and print labels, wire wraps and shrink tube.

New features include auto sizing, fast print speeds, quick response time, scaleable fonts, downloadable fonts, more memory to store label formats and fonts and a print resolution of 300 dpi. **K4100** also uses the same cartridge system as the **K5100**, **K2500** and **K3000-PC**.

### K4100 Features

- Thermal transfer print technology
- Two line x 16 character LCD display
- Prints 6-72 point at 300 dpi resolution
- Prints up to 6 lines of text
- Use stand alone or with you PC
- Downloadable scaleable fonts
- On-board memory to store label formats and fonts
- Flash upgradeable firmware
- 10 resident codes including Code 39 and Code 128
- Multi-language prompts including English and Spanish
- Alpha/Numeric sequencing (A-Z, 1-999)
- Repeat function allows up to 999 copies
- Built-in cutter and feed control to eliminate waste
- Print styles include frame, bold, italic, underline and mirror
- Rotate feature for landscape or portrait mode
- Vertical and horizontal print formats

### K4100 Printer and Accessories

**Part Number**  
2562000

**Description**  
**K4100** Desktop Printer  
Includes: **K4100** Printer, Manual, AC Adapter, Power Cord and Serial Cable

**Part Number**  
2563000  
2558800  
2562900

**Accessories**  
AC Adapter (110V)  
Serial Cable  
Carrying Case

### K4100 Physical Dimensions

9.50" L x 8" D x 2.75" H

### K4100 Electrical Specifications

- AC Adapter Input: 100-250 VAC, 50/60 Hz, 43W; AC Adapter Output: 12 DVC, UL, C-UL, CE
- Meets VDE-B and FCC Part 15 class B RFI limits
- RS 232 Serial Port, 9600-115200 baud