



www.impactwiremarking.com

Product Data Sheet -730 THL Thermal Transfer Film-

General Description:

Impact's 730 THL film is a 2.0 mil gloss top coated thermal transfer printable silver polyester material with an aggressive, permanent solvent-based acrylic adhesive, and backed with a roll form release liner. Film recognized under UL file number MH16635 and CSA standard C22.2 No. 0.15-95

PRODUCT DATA	VALUE
--------------	-------

Physical Properties

Thickness	film:	2.0
mil	adhesive:	0.8-0.9
	liner:	3.1

Dimensional Stability (%)	no shrinkage
---------------------------	--------------

Adhesion Properties

Adhesion from	Expected Range oz/in
---------------	-------------------------

Stainless Steel	50-85
Acrylic	55-90

Glass	55-90
-------	-------

Expected Sheer (hours)	100
---------------------------	-----

EXPECTED EXTERIOR LIFE	2 yrs.
SERVICE TEMP. RANGE	-40°F to 302°F
MINIMUM APPLICATION TEMP.	50°F
STORAGE STABILITY	2 yrs @ 70°F and 50%RH

Although the information and recommendations set forth herein are presented in good faith and believed to be correct as of this date, Impact, Inc. makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the person receiving the same will make their own determination as to the suitability for their purpose.